

High Speed Colour Duplex Scanner

# *fi*-5530C2 Image Scanner



100 images per minute scanning speed  
@200 dpi, colour or monochrome

Auto colour detection, blank page deletion,  
auto cropping, and auto de-skew

100 page automatic document feeder

Ultrasonic multi-feed detection

Kofax VRS® 4 processing delivers excellent  
image quality

1 year warranty

**ADOBE** ACROBAT® 8 STANDARD



**FUJITSU**

THE POSSIBILITIES ARE INFINITE



### Excellent scanning and cost performance

The fi-5530C2's ability to scan 50 pages / 100 images per minute in landscape (200 dpi) and 35 pages / 70 images per minute in portrait (200 dpi) enables operators to quickly and efficiently digitize large amount of papers.

### Includes the newest "ScandAll PRO" image capturing software

"ScandAll PRO" image capturing software is loaded with many useful scanning functions:

- Scan to email, scan to print, scan to file, scan to FTP, scan to PDF, and scan to Microsoft SharePoint Server.

- Searchable PDF, compressed PDF, password protected PDF, single page display PDF, PDF/A (ISO-19005-1), TIFF, MTIF, JPEG, J2K, and BMP.



### Post imprinter support

The fi-5530C2 supports an imprinter option that is capable of printing dates and other information on the back of scanned documents in order to simplify the search for the original document at a later date.

### Kofax® VRS (Virtual ReScan) bundled

Advantages of VRS include:

- VRS verification and adjustment features generate perfect images every time.

- The ability to efficiently digitize large volumes of documents dramatically improves scanning productivity.

- Easy to use. Automated functions remove the need for skilled scanner operators.

1) Actual scanning speeds are affected by data transmission and software processing times.

2) Using JPEG compression.

3) For 2" x 3" document, paper weight must be 34 lb.

Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe, Acrobat, Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Kofax, VirtualReScan, Adrenaline and the "VRS VirtualReScan" logo are registered trademarks of Kofax Image Products. All the other trademarks mentioned herein are the property of their respective owners. Specifications are subject to change without notice. © 2007 Fujitsu Canada, Inc. All rights reserved. FCI-09-18.2007-E

### TECHNICAL SPECIFICATIONS

<b>Scanner type</b>	ADF (Automatic Document Feeder)	
<b>Scanning modes</b>	Simplex / Duplex Colour / Greyscale / Monochrome	
<b>Image sensor type</b>	Dual colour CCDs (Charged Coupled Device)	
<b>Light source</b>	White fluorescent lamp	
<b>Scanning range</b>	<i>Minimum</i>	2.0" x 2.9" (52 x 74 mm) <sup>3</sup>
	<i>Maximum</i>	11" x 34" (297 x 863 mm)
<b>Paper weight (Thickness)</b>	14 to 34 lb. ISO 7810 plastic cards (not embossed)	
<b>Scanning speed<sup>1</sup> (Letter, Landscape, 200 dpi)</b>	50 ppm / 100 ipm (colour <sup>2</sup> , greyscale <sup>2</sup> , or monochrome)	
<b>Paper chute capacity</b>	Max. 100 sheets (Letter, 20 lb.) Max. 50 sheets (11"x17", 20 lb.)	
<b>Background</b>	Black and white (auto-switching)	
<b>Optical resolution</b>	600 dpi	
<b>Output resolution</b>	50 to 600 dpi	
<b>Output format</b>	24 bit (colour), 8 bit (greyscale), or 1 bit (monochrome).	
<b>AD converter</b>	10 bit	
<b>Drivers</b>	TWAIN and ISIS™	
<b>Interfaces</b>	Ultra SCSI / USB2.0 (auto switching)	
<b>Connector shape</b>	<i>SCSI</i>	Shield type 68-pin (pin type)
	<i>USB</i>	B Type
<b>SCSI terminator</b>	Built-in	
<b>Output mode (Half-tone)</b>	Dither / Error diffusion	
<b>Voltage</b>	AC 100 to 240 V, 50/60 Hz	
<b>Power</b>	<i>Operating</i>	57 watts or less
	<i>Sleep mode</i>	Less than 7.5 watts
<b>Operational environment</b>	<i>Temperature</i>	5°C to 35°C (42°F to 95°F)
	<i>Relative humidity</i>	20% to 80% (non-condensing)
<b>Dimensions (W x D x H)</b>	399 mm x 225 mm x 193 mm (15.7" x 8.8" x 7.5")	
<b>Weight</b>	8.5 kg (18.7 lb.)	
<b>Environmental compatibility</b>	EnergyStar® and RoHS	
<b>Other</b>	<i>Multi-feed detection</i>	Standard; Ultrasonic multi-feed detection sensor.
	<i>TWAIN functions</i>	Auto crop, auto de-skew, auto colour detection, blank page detection.
	<i>Dropout colour</i>	Selectable dropout colour (red, green, blue, or none).

### OPTIONS

<b>Post-scanning imprinter (FI-553PR)</b> PA03334-D401	Assists document management by printing numbers, letters and codes on original document after they have been scanned.
<b>Image processing software v2.5</b> PA43402-C22901	This image processing software provides additional image clean-up functions when difficult documents are being scanned.

### CONSUMABLES

<b>ScanAid kit</b> CG01000-505101	Up to 400,000 sheets or 1 year. The kit includes 2 pick rollers, 5 pad assemblies, and 1 cleaning kit.
<b>Print Cartridge for FI-553PR</b> CA00050-0262	Up to 4,000,000 printed characters.

### SERVICE OPTIONS

<b>Post warranty maintenance coverage</b>	Provides post warranty remedial maintenance.
---	--

### BUNDLED ITEMS

	AC power cable, Installation guide, Adobe® Acrobat® 8.0 Standard, ScandAll Pro, ISIS/TWAIN drivers, Kofax VRS® 4 Basic.
--	---

### WARRANTY

	1 year return to depot. Visit <a href="http://www.fujitsu.ca/warranty/scanner/">www.fujitsu.ca/warranty/scanner/</a> for more details.
--	---



MultiCIM Technologies Inc.  
14 Westminster N, suite 306C  
Montreal West, QC, CANADA H4X 1Y8  
T : (514) 633-6401 or 1 (877) MULTICIM  
F : (514) 633-6495  
sales@exadox.com



THE POSSIBILITIES ARE INFINITE